

Before ordering servers or workstations please confirm the specifications shown below with Impact Technologies as specifications are subject to change without notice.

Impact Technologies leverages web collaboration technologies for remote installation and support. This requires the Impact Technologies technical support team be provided remote access to all servers and workstations.

Server for Application and Web Services

The server configuration for hosting the Traffic Analyst application depends on the Traffic Analyst modules in use, the switches and the means of communication.

	Dedicated	Virtual Machine
Processor Minimum	Two (2) Processors: 2 GHz Intel Xeon Quad Core	Three (3) Cores assigned to Traffic Analyst
Memory Minimum	10 GB 1333 MHz optimized for two (2) processors	10 GB with 8 GB dedicated/reserved
Disk Storage	<ul style="list-style-type: none"> ◆ Minimum: 500 GB available to application ◆ Minimum: 10,000 RPM hard drive 	<ul style="list-style-type: none"> ◆ Minimum: 500 GB ◆ 10,000 RPM hard drive, iSCSI or FiberChannel
Operating System	<ul style="list-style-type: none"> ◆ Windows Server 2019 (Standard Edition) ◆ Windows Server 2016 (Standard Edition) ◆ Windows Server 2012 R2 (Standard Edition) ◆ Disable UAC ◆ Internet Information Services (IIS) 8.0 - Windows Server 2012 ◆ Internet Information Services (IIS) 10.0 	
Open/Unblocked Network Ports	20: Telnet control 21: FTP 22: SFTP (required only for Unify OpenScape Voice switch) 23: Telnet 25: SMTP (E-mail) 80: Web access 162: QoS SNMP traps (optional, only for Unify OpenScape Voice or HiPath 4000 QoS data collection) 513: rlogin (Nortel switch only) 2638: Database 4001: Traffic Analyst Client access 8443: Cisco UCM (for extensions and route pool and trunk group names API) 8768: Unify OpenScape Voice (for route pool and trunk group names API) 9999: Lantronix (optional, only if using Lantronix UDS-10 to convert serial communication to IP) 10001: Lantronix (optional, only if using Lantronix UDS-10 to convert serial communication to IP) 27069: Required only for Unify HiPath 3000	
Other	<ul style="list-style-type: none"> ◆ CD ROM drive, keyboard and mouse ◆ Monitor ◆ Printer - network or local ◆ Network interface card with 100Mbps connection ◆ 2nd Network interface card with 100Mbps connection (optional, only for Unify OpenScape Voice or HiPath 4000 QoS data collection if phones on separate network) ◆ SMTP Mail Server must be accessible and configured if e-mail service is to be performed (optional) ◆ Microsoft Internet Explorer 8, 9, 10 or 11 ◆ Microsoft Silverlight 5.x ◆ .NET Framework v 4.7 ◆ SNMP Services and SNMP Trap (optional, only for Unify OpenScape Voice or HiPath 4000 QoS data collection) ◆ FTP or SFTP server for data collection (required for Cisco UCM; optional for Unify OpenScape Voice) 	

End User Workstation for Dashboard

Operating System	<ul style="list-style-type: none">◆ Windows 10◆ Windows 8◆ Windows 7 (64 bit)
Processor	<ul style="list-style-type: none">◆ Minimum: Intel Core i5 2400 Processor (3.1 GHz, 6M) or equivalent
Memory	<ul style="list-style-type: none">◆ Minimum: 4 GB
Disk Space	<ul style="list-style-type: none">◆ Minimum: 10 GB
Open & Available Network Ports	80: Web access
Other	<ul style="list-style-type: none">◆ Keyboard and mouse◆ Monitor capable of 1600 X 1024 resolution◆ Printer: network or local◆ Network Interface Card (Minimum: 100 Mb LAN)◆ Microsoft Internet Explorer 8, 9, 10 or 11◆ Microsoft Silverlight 5.x◆ .Net Framework V4.7◆ PDF reader◆ Microsoft Excel